



Introlab

outperform the norm

MAXI-ANTIFOAM



CATEGORY Adjuvant Range
REG.NO.: Act 36 of 1947



PRODUCT DESCRIPTION

Maxi-Antifoam is a silicone-based antifoaming or defoaming agent for the suppression and prevention of foam formation in spray solutions.

GUARANTEED ANALYSIS (g/L)

Polydimethylsiloxane, Dimethyl siloxane - 100 g/L

FORMULATION TYPE

Liquid - White Antifoam Emulsion

FEATURES & BENEFITS

- **Maxi-Antifoam** is a defoaming agent for the suppression and prevention of foam formation in spray solutions.

PHYSICAL CHARACTERISTICS

- Physical State - Liquid
- Density (at 20°C) - 1.00 ± 0.02

APPLICATION RATES

Refer to product label for complete application rates per crop

COMPATIBILITY

Relevant uses for Agriculture, Antifoam / Defoaming agent for suppression of foam in the spray tank.

HANDELING & PRECAUTIONS

- Store in the original, well-sealed container away from direct sunlight in a cool dry environment.
- Keep away from children, uninformed people, animals and foodstuffs.
- Do not re-use the container

PACKAGING 1L | 5L | 10L | 20L | 200L | 1000L

APPLICATION TIMING

- Apply 20 ml **Maxi-Antifoam** per 100 L water (or spray mixture) prior to or after the formation of problematic foam in the spray tank.
- To ensure good emulsification, pre-mix this product with water before adding it to the spray mixture

APPLICATION METHODS

Maxi-Antifoam can be applied by: Boom sprayer | Knapsack | Irrigation system

HEAD OFFICE 12 Oudepoort Street,
Wellington Industrial Park, Wellington, South Africa
TEL +27 21 864 2145 / 6
GENERAL EMAIL info@introlab.co.za



GAUTENG OFFICE 322 Marks Street,
Waltloo, Pretoria, South Africa
TEL +27 12 803 2011
WEB www.introlab.co.za

